

Technical data KNX-IP Interface



device may not be connected to 230V!

Current consumption	< 40 mA	
Connections	IP line: RJ45 socket for 100 Mbit and 10 Mbit BaseT, IEEE 802.3 networks KNX line: KNX bus WAGO connector (red/black), screwless for single-core cable Ø 0,6...0,8 mm	
Display elements	LED Bus state LED "Program Mode"	LED Traffic LED Error
Control elements	Function button, Program button	
Mounting	35 mm top-hat rail (TH35) according to IEC60715	
Protection type	IP20 according to IEC60529	
Pollution degree	2 according to IEC60664-1	
Protection class	III according to IEC61140	
Overvoltage category	II according to IEC60664-1	
Approbation	KNX-certified according to ISO/IEC14543-3	
CE-Marking	According to low voltage and EMC guidelines Compliance: EN50428, EN50581, EN61000-6, EN62479	
Power supply	Safety extra low voltage, 21...30V DC (SELV)	
Housing colour	Plastic PA66 housing grey	
Dimensions	H = 90 mm, W = 36 mm (2 modules), D = 71 mm Mounting depth = 64 mm	
Weight	70 g	
Device temperature	Working temperature: -5...45 °C Storage temperature: -20...60 °C	
Ambient humidity	5...93 %, non-condensing	